

6 LED LIGHT MODULE

AMS lights are installed at 6m to 9m spans along the electrified fence line to enlighten the area. At the point when the electric fence catalyst alerts, the edge caution lights will enlighten the particular zone that has been set off. This could help identify, and hence deflect, the gatecrasher from going after the fence line. The lights are LED, consuming low energy, and will be enlightened right away.



AVAILABLE IN

- The system is powered by a 2.0Amp AMS Power Load with a 7Ah battery for reinforcement during power disappointments
- A solitary power pack can give capacity to 20 sets of lights (40 altogether)
- Lights are installed at 6m to 9m stretches along the wall line with 200m inclusion on a power pack
- Lights are descending facing
- Lights are LED significance no warm-up time is required
- Lights can be set off in three ways:
Energizer caution trigger
Remote on and off
Day/night switch
- Wet/dry contacts are configurable on the power-supply trigger module
- Low-voltage cabling is run along the wall line to give capacity to the lights



SPECIFICATIONS

Illumination angle	20°
IP rating	IP67
Input voltage	20 – 30VDC
Emission colour	Ultra bright white
Current consumption	20mA
Mounting	2 x 5mm holes
Operating temperature	-20° – 55°C
Minimum luminous intensity	99000mcd

STOCK CODE	DESCRIPTION
AM-FL/6LED-4	6 LED Light Module

02 YEARS WARRANTY

